



QC CL-2250  
QuietCool Original Classic Line

**QC CL-2250 Specifications**

Air Flow	Hi: 2,465 CFM / Low: 1,910 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 1,770 CFM / Low: 1,330 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 822 SQFT to 1,233 SQFT
Energy Use	Hi: 250 Watts / Low: 201 Watts
Amps	Hi: 2.47 / Low: 1.90
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 43.2 / Low: 37.4
Minimum Attic Clearance	34"
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	3.29 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 18 1/4"
Removable Grille Outside Dimension	16" x 20"
Shipping Weight	48 lbs.
Box Dimensions	24" x 20" x 38"
In The Box	-QC CL-2250 Motorhead    -Damper Box -Ceiling Grille            -6 Foot Duct -Cut-out Template        -Accessory Bag -Window Locks



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)