



QC CL-2250 Specifications

| Motor Voltage | 120 VAC, 60 Hz | |
|--|--|----------------|
| Energy Use | Hi: 250 Watts / Low: 201 Watts | |
| Air Flow | Hi: 2465 CFM / Low: 1910 CFM | |
| HVI-916 Airflow (for CA Title 24 New Construction) | 1770 CFM | |
| dBA | Hi: 42.7 / Low: 37.4 | |
| Recommended SQFT Coverage @ 2 CFM per SQ FT | Covers 822 SQFT to 1233 SQFT | |
| # of Speeds | 2 | |
| Duct Diameter | 16" | |
| Duct Length | 6 feet | |
| Motor Head Diameter | 16 1/2" | |
| Motor Head Length | 13 1/2" | |
| Dampers | Barometric Pressurized R5 Dampers | |
| Controls (Not Included) | Recommended 8 Hour Electronic Timer (IT-30070) and | |
| | HI-LOW-OFF Switch (IT-35000) | |
| Warranty | 10 Years | |
| Framing | None Required | |
| Joist Cutting | None Required; fits 16" or 24" on center | |
| Minimum Suggested Attic Venting | 3.29 SQ FT net free area | |
| Ceiling Rough Opening | 14 1/4" x 18 1/4" | |
| Removable Grille Outside Dimension | 16" × 20" | |
| Shipping Weight | 48 lbs. | |
| Box Dimensions | 24" × 20" × 38" | |
| In The Box | -QC CL-2250 Motorhead | -Damper Box |
| | -Ceiling Grille | -6 Foot Duct |
| | -Cut-out Template | -Accessory Bag |
| | -Window Locks | |



For more information, visit our website at: QUIETCOOLSYSTEMS.COM