



QC CL-3100
QuietCool Original Classic Line

QC CL-3100 Specifications

Air Flow	Hi: 3,126 CFM / Low: 2,847 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 2,380 CFM / Low: 2,160 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,072 SQFT to 1,608 SQFT
Energy Use	Hi: 299 Watts / Low: 256 Watts
Amps	Hi: 2.58 / Low: 2.20
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 49.4 / Low: 46.8
Minimum Attic Clearance	34"
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	4.17 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 22 1/4"
Removable Grille Outside Dimension	16" x 24"
Shipping Weight	56 lbs.
Box Dimensions	27" x 20" x 38"
In The Box	-QC CL-3100 Motorhead -Damper Box -Ceiling Grille -6 Foot Duct -Cut-out Template -Accessory Bag -Window Locks



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM