



QC CL-4700  
QuietCool Original Classic Line

**QC CL-4700 Specifications**

Air Flow	Hi: 4,415 CFM / Low: 3,402 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,230 CFM / Low: 2,560 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,472 SQFT to 2,207.5 SQFT
Energy Use	Hi: 551 Watts / Low: 415 Watts
Amps	Hi: 4.73 / Low: 3.54
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 49.4 / Low: 43.2
Minimum Attic Clearance	36"
Duct Diameter	16"
Duct Length	9 feet
Motor Head Diameter	18 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	5.89 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	75 lbs.
Box Dimensions	36" x 22" x 40"
In The Box	-QC CL-4700 Motorhead    -Damper Box -Ceiling Grille            -9 Foot Duct -Cut-out Template        -Accessory Bag -Window Locks



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)