

**QC CL-4700 Specifications**

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 551 Watts / Low: 415 Watts	
Air Flow	Hi: 4415 CFM / Low: 3402 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3230 CFM / Low: 2560 CFM	
dBA	Hi: 49.4 / Low: 41.6	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1472 SQFT to 2207.5 SQFT	
Minimum Attic Clearance	36"	
# of Speeds	2	
Duct Diameter	18"	
Duct Length	9 feet	
Motor Head Diameter	18 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	5.89 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	36" x 22" x 40"	
In The Box	-QC CL-4700 Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag

