



QC CL-5400
QuietCool Original Classic Line

QC CL-5400 Specifications

| | | |
|----------------------------------------------------|--------------------------------------------------------------------------------|-----------------------------------------------|
| Motor Voltage | 120 VAC, 60 Hz | |
| Energy Use | Hi: 634 Watts / Low: 525 Watts | |
| Air Flow | Hi: 5024 CFM / Low: 4406 CFM | |
| HVI-916 Airflow (for CA Title 24 New Construction) | Hi: 3950 CFM / Low: 3240 CFM | |
| dBA | Hi: 51.2 / Low: 43.6 | |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT | Covers 1675 SQFT to 2512 SQFT | |
| Minimum Attic Clearance | 38" | |
| # of Speeds | 2 | |
| Duct Diameter | 20" | |
| Duct Length | 9 feet | |
| Motor Head Diameter | 20 1/2" | |
| Motor Head Length | 13 1/2" | |
| Dampers | Barometric Pressurized R5 Dampers | |
| Controls (Sold Separately) | Recommended: IT-36002 QuietCool RF Wireless Control Kit | |
| Warranty | 10 Years | |
| Framing | None Required | |
| Joist Cutting | None Required; fits 16" or 24" on center | |
| Minimum Suggested Attic Venting | 6.7 SQ FT net free area | |
| Ceiling Rough Opening | 14 1/4" x 30 1/4" | |
| Removable Grille Outside Dimension | 16" x 32" | |
| Shipping Weight | 75 lbs. | |
| Box Dimensions | 39" x 24" x 39" | |
| In The Box | -QC CL-5400 Motorhead -Ceiling Grille -Cut-out Template -Window Locks | -Damper Box -9 Foot Duct -Accessory Bag |



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM