



QC CL-6000
QuietCool Original Classic Line

QC CL-6000 Specifications

Air Flow	Hi: 5,665 CFM / Low: 4,289 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 4,160 CFM / Low: 3,200 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,888 SQFT to 2,833 SQFT	
Energy Use	Hi: 769 Watts / Low: 560 Watts	
Amps	Hi: 6.90 / Low: 5.09	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 51.1 / Low: 44.1	
Minimum Attic Clearance	42"	
Duct Diameter	22"	
Duct Length	9 feet	
Motor Head Diameter	22 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	7.56 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	91 lbs.	
Box Dimensions	41" x 26" x 39"	
In The Box	-QC CL-600 Motorhead -Damper Box -Ceiling Grille -9 Foot Duct -Cut-out Template -Accessory Bag -Window Locks	



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM