

**QC CL-6000 Specifications**

|  |  |   |
|--|--|---|
| Motor Voltage                                      | 120 VAC, 60 Hz   |   |
| Energy Use   | Hi: 769 Watts / Low: 560 Watts   |   |
| Air Flow   | Hi: 5665 CFM / Low: 4289 CFM   |   |
| HVI-916 Airflow (for CA Title 24 New Construction) | Hi: 4160 CFM / Low: 3200 CFM   |   |
| dBA  | Hi: 49.3 / Low: 42.5   |   |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT       | Covers 1888 SQFT to 2833 SQFT  |   |
| Minimum Attic Clearance                            | 42"  |   |
| # of Speeds  | 2  |   |
| Duct Diameter                                      | 22"  |   |
| Duct Length  | 9 feet   |   |
| Motor Head Diameter                                | 22 1/2"  |   |
| Motor Head Length                                  | 13 1/2"  |   |
| Dampers  | Barometric Pressurized R5 Dampers  |   |
| Controls (Sold Separately)                         | Recommended: IT-36002 QuietCool RF Wireless Control Kit                        |   |
| Warranty   | 10 Years   |   |
| Framing  | None Required  |   |
| Joist Cutting                                      | None Required; fits 16" or 24" on center                                       |   |
| Minimum Suggested Attic Venting                    | 7.56 SQ FT net free area   |   |
| Ceiling Rough Opening                              | 14 1/4" x 36 1/4"  |   |
| Removable Grille Outside Dimension                 | 16" x 38"  |   |
| Shipping Weight                                    | 91 lbs.  |   |
| Box Dimensions                                     | 41" x 26" x 39"  |   |
| In The Box   | -QC CL-6000 Motorhead<br>-Ceiling Grille<br>-Cut-out Template<br>-Window Locks | -Damper Box<br>-9 Foot Duct<br>-Accessory Bag |

