



QC CL-6000
QuietCool Original Classic Line

QC CL-6000 Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 769 Watts / Low: 560 Watts	
Air Flow	Hi: 5665 CFM / Low: 4289 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	4160 CFM	
dBA	Hi: 49.3 / Low: 42.5	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers 1888 SQFT to 2833 SQFT	
# of Speeds	2	
Duct Diameter	22"	
Duct Length	9 feet	
Motor Head Diameter	22 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Not Included)	Recommended 8 Hour Electronic Timer (IT-30070) and HI-LOW-OFF Switch (IT-35000)	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	7.56 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	103 lbs.	
Box Dimensions	41" x 26" x 39"	
In The Box	-QC CL-6000 Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM