



QC CL-7000
QuietCool Original Classic Line

QC CL-7000 Specifications

| | |
|--|---|
| Air Flow | Hi: 6,924 CFM / Low: 5,518 CFM |
| HVI-916 Airflow (for CA Title 24 New Construction) | Hi: 5,300 CFM / Low: 4,100 CFM |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT | Covers 2,308 SQFT to 3,462 SQFT |
| Energy Use | Hi: 1,147 Watts / Low: 794 Watts |
| Amps | Hi: 9.61 / Low: 7.12 |
| Motor Voltage | 120 VAC, 60 Hz |
| # of Speeds | 2 |
| dBA | Hi: 54.3 / Low: 47.4 |
| Minimum Attic Clearance | 44" |
| Duct Diameter | 24" |
| Duct Length | 9 feet |
| Motor Head Diameter | 24 1/2" |
| Motor Head Length | 13 1/2" |
| Dampers | Barometric Pressurized R5 Dampers |
| Controls (Sold Separately) | Recommended: IT-36002 QuietCool RF Wireless Control Kit |
| Warranty | 10 Years |
| Framing | None Required |
| Joist Cutting | None Required; fits 16" or 24" on center |
| Minimum Suggested Attic Venting | 9.24 SQ FT net free area |
| Ceiling Rough Opening | 14 1/4" x 36 1/4" |
| Removable Grille Outside Dimension | 16" x 38" |
| Shipping Weight | 95 lbs. |
| Box Dimensions | 41" x 28" x 39" |
| In The Box | -QC CL-7000 Motorhead -Damper Box -Ceiling Grille -9 Foot Duct -Cut-out Template -Accessory Bag -Window Locks |



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM