

QC ES-1500 Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	64.5 Watts	
Air Flow	1434 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	1010 CFM	
dBA	Hi: 37.2	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 478 SQFT to 717 SQFT	
Minimum Attic Clearance	32"	
# of Speeds	1	
Duct Diameter	14"	
Duct Length	6 feet	
Motor Head Diameter	14 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	1.92 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 14 1/4"	
Removable Grille Outside Dimension	16" x 16"	
Shipping Weight	40 lbs.	
Box Dimensions	20" x 20" x 38"	
In The Box	-QC ES-1500 Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -6 Foot Duct -Accessory Bag



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

QC ES-1500
QuietCool Energy Saver Line