



QC ES-2250
QuietCool Energy Saver Line

QC ES-2250 Specifications

Air Flow	Hi: 2,492 CFM / Low: 1,991 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 1,850 CFM / Low: 1,420 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 831 SQFT to 1,246 SQFT
Energy Use	Hi: 150 Watts / Low: 79.5 Watts
Amps	Hi: 2.04 / Low: 1.10
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 42.7 / Low: 37.2
Minimum Attic Clearance	34"
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	3.33 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 18 1/4"
Removable Grille Outside Dimension	16" x 20"
Shipping Weight	48 lbs.
Box Dimensions	24" x 20" x 38"
In The Box	-QC ES-2250 Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -6 Foot Duct -Accessory Bag



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM