



QC ES-2250  
QuietCool Energy Saver Line

**QC ES-2250 Specifications**

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 150 Watts / Low: 79.5 Watts	
Air Flow	Hi: 2492 CFM / Low: 1991 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	1850 CFM	
dBA	Hi: 43.2 / Low: 37.2	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 1250 SQ FT	
# of Speeds	2	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Not Included)	Recommended 8 Hour Electronic Timer (IT-30070) and HI-LOW-OFF Switch (IT-35000)	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	3.33 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 18 1/4"	
Removable Grille Outside Dimension	16" x 20"	
Shipping Weight	48 lbs.	
Box Dimensions	24" x 20" x 38"	
In The Box	-QC ES-2250 Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -6 Foot Duct -Accessory Bag



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)