

QC ES-4700 Specifications

Air Flow	Hi: 4,195 CFM / Low: 2,304 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,080 CFM / Low: 1,620 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,398 SQFT to 2,098 SQFT
Energy Use	Hi: 415 Watts / Low: 75 Watts
Amps	Hi: 5.07 / Low: 1.03
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 47.4 / Low: 33.0
Minimum Attic Clearance	36"
Duct Diameter	18"
Duct Length	9 feet
Motor Head Diameter	18 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	5.6 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	75 lbs.
Box Dimensions	36" x 22" x 40"
In The Box	-QC ES-4700 Motorhead -Damper Box -Ceiling Grille -9 Foot Duct -Cut-out Template -Accessory Bag -Window Locks



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

QC ES-4700
QuietCool Energy Saver Line