

QC ES-5400 Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 497 Watts / Low: 88.9 Watts	
Air Flow	Hi: 5003 CFM / Low: 2842 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3810 CFM / Low: 2020 CFM	
dBA	Hi: 50.7 / Low: 35.6	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1667 SQFT to 2502 SQFT	
Minimum Attic Clearance	38"	
# of Speeds	2	
Duct Diameter	20"	
Duct Length	9 feet	
Motor Head Diameter	20 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	6.68 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	39" x 24" x 39"	
In The Box	<ul style="list-style-type: none"> -QC ES-5400 Motorhead -Ceiling Grille -Cut-out Template -Window Locks 	<ul style="list-style-type: none"> -Damper Box -9 Foot Duct -Accessory Bag

