

QC ES-6000 Specifications

Air Flow	Hi: 5,576 CFM / Low: 3,417 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 4,040 CFM / Low: 2,450
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,859 SQFT to 2,788 SQFT
Energy Use	Hi: 455 Watts / Low: 112 Watts
Amps	Hi: 5.68 / Low: 1.65
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 49.3 / Low: 38.5
Minimum Attic Clearance	42"
Duct Diameter	22"
Duct Length	9 feet
Motor Head Diameter	22 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	7.44 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 36 1/4"
Removable Grille Outside Dimension	16" x 38"
Shipping Weight	91 lbs.
Box Dimensions	41" x 26" x 39"
In The Box	-QC ES-6000 Motorhead -Damper Box -Ceiling Grille -9 Foot Duct -Cut-out Template -Accessory Bag -Window Locks



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

QC ES-6000
QuietCool Energy Saver Line