

## QC ES-7000 Specifications

Air Flow	Hi: 6,878 CFM / Low: 4,304 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 5,170 CFM / Low: 3,150 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 2,293 SQFT to 3,439 SQFT
Energy Use	Hi: 727 Watts / Low: 164 Watts
Amps	Hi: 8.96 / Low: 2.32
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 51.7 / Low: 41.4
Minimum Attic Clearance	44"
Duct Diameter	24"
Duct Length	9 feet
Motor Head Diameter	24 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit
Warranty	10 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	9.18 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 36 1/4"
Removable Grille Outside Dimension	16" x 38"
Shipping Weight	95 lbs.
Box Dimensions	41" x 28" x 39"
In The Box	-QC ES-7000 Motorhead    -Damper Box -Ceiling Grille            -9 Foot Duct -Cut-out Template        -Accessory Bag -Window Locks



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)

QC ES-7000  
QuietCool Energy Saver Line