

QC ES-7000 Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 727 Watts / Low: 164 Watts	
Air Flow	Hi: 6878 CFM / Low: 4304 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 5170 CFM / Low: 3150 CFM	
dBA	Hi: 54.3 / Low: 41.4	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 2293 SQFT to 3439 SQFT	
Minimum Attic Clearance	44"	
# of Speeds	2	
Duct Diameter	24"	
Duct Length	9 feet	
Motor Head Diameter	24 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Sold Separately)	Recommended: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	9.18 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	95 lbs.	
Box Dimensions	41" x 28" x 39"	
In The Box	-QC ES-7000 Motorhead -Ceiling Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

QC ES-7000
QuietCool Energy Saver Line