



**QC STL PRO-4.8X**  
**QuietCool Stealth Pro Line**

**QC STL PRO-4.8X Specifications**

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 408 Watts / Med: 225 Watts / Low: 73.9 Watts	
Air Flow	Hi:4280 CFM / Med:3500 CFM / Low:2361 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	3130 CFM	
dBA	Hi: 47.4 / Med: 43.2 / Low: 33.0	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers 1427 SQFT to 2140 SQFT	
# of Speeds	3	
Duct Diameter	18"	
Duct Length	9 feet	
Motor Head Diameter	18 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	5.71 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	36" x 22" x 40"	
In The Box	-QC STL PRO-4.8X Motorhead -Removable Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)