

**QC TRI PRO-7.0X**  
**QuietCool Trident Pro Line**

**QC TRI PRO-7.0X Specifications**

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 1147 Watts / Low: 797 Watts	
Air Flow	Hi: 7015 CFM / Low: 5548 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 5300 CFM / Low: 4150 CFM	
dBA	Hi: 51.7 / Low: 45.3	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 2338 SQFT to 3507 SQFT	
Minimum Attic Clearance	44"	
# of Speeds	2	
Duct Diameter	24"	
Duct Length	9 feet	
Motor Head Diameter	24 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included: 8 Hr Electronic Timer & HI-LOW-OFF switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	9.36 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	97 lbs.	
Box Dimensions	41" x 28" x 39"	
In The Box	-QC TRI PRO-7.0X Motorhead -Removable Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)