

RM WHF-4.0-DG1 Specifications

Airflow	Hi: 3,543 CFM / Med: 3,205 CFM / Low: 2,878 CFM
	<u>'</u>
HVI-916 Airflow (for CA Title 24 New Construction)*	Hi: 2,582 CFM / Med: 2,336 CFM / Low: 2,068 CFM
Energy Use	Hi: 451 Watts / Med: 316 Watts / Low: 219 Watts
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,220 SQFT to 1,831 SQFT
Amps	Hi: 5.5 / Med: 3.9 / Low: 2.8
Motor Voltage	120VAC, 60 Hz
# of Speeds	3
Minimum Chase Clearance	5.5"
Motor Head Diameter	24.75"
Dampers	Barometric Pressurized Dampers 22" x 22"
Controls	IT-36002 QuietCool RF Wireless Control Kit
Warranty	15 Years
Framing: Roof Rafter	24" on center
Framing: Ceiling Joist	24" on center
Minimum Suggested Attic Venting	None
Roof Opening	22" circle
Damper Grille Outer Dimension	24" x 24"
Ceiling Rough Opening	22.25" x 22.25"
Flashing Dimensions	36" x 36"
Roof Cap Dimensions	39.5" x 39.5"
Overall Height	15"
Shipping Package 1: Fan	69 lbs.
Shipping Package 2: Accessories	9 lbs.
Box Dimensions: Fan	42" × 20" × 44"
Box Dimensions: Accessories	24" x 24" x 3.5"
In The Box	- RM WHF-4.0 Fan - Accessory Bag
	- (1) Damper Ceiling Grille - Cut-out Template





* Varies on application of the home. These numbers are estimated. For more information, visit our website at: QUIETCOOLSYSTEMS.COM