



# AFR PRO-1.3 QuietCool Advanced Roof Mount Fan

## AFR PRO-1.3 Specifications

Airflow	Hi: 1,266 CFM / Low: 834 CFM
HVI-916 / 920 Airflow (for CA)	Hi: 984 CFM / Low: 649 CFM
Attic SQFT Coverage @ .75 CFM per SQFT	Covers up to 1,750 SQFT
Energy Use	Hi: 120 Watts / Low: 75.5 Watts
CFM/Watt	Hi: 10.55 / Low: 11.05
Amps	Hi: 1.14 / Low: 0.69
Motor Voltage	120 VAC, 60 Hz
# of Fan Speeds	2
Housing Diameter	16 3/4"
Rough Cut-out Diameter	17 1/4"
Overall Height	10.25"
Roof Cap Dimension	28" x 28"
Flashing	26" x 26"
Cover to Flashing Clearance	4 1/2"
Primary Flashing (included)	For roofs 3:12 to 8:12 pitch
Curb Flashing - FLA-CRB-2222 (sold separately)	For flat roofs 3:12 pitch and below
Secondary Flashing - FLA-SEC-3743 (sold separately)	For tile/cement roofs 3:12 to 8:12 pitch
Wildlife Guard	0.25" diameter holes
Paint Coating	High-quality Hybrid Black Polyester Paint Premium film integrity and extreme UV protection from fade and chalk
Controls	IT-30002 Thermostat (included)
Fire Safety Sense Shut-off	182 °F
Warranty	15 Years
Shipping Weight	31 lbs.
Box Dimensions	31" x 31" x 14"
In The Box	- AFR SMT PRO-1.3 - Accessory Bag - Smart Control Hub - Cut-out Template

### Features & Benefits:

- 2-speed Energy Efficient PSC motor
- QuietCool Adjustable Thermostat
- 20 foot power cord attached
- Plug and play (no wiring required)



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)

