

AFG SMT ES-3.0 Specifications

Airflow	Hi: 2,801 CFM / Med: 2,041 CFM / Low: 1,337 CFM
HVI-916 Airflow (w/ standard louver) (for CA)*	Hi: 1,400 CFM / Med: 1,000 CFM / Low: 620 CFM
Energy Use	Hi: 142 Watts / Med: 73.1 Watts / Low: 23.1 Watts
Attic SQFT Coverage @ .75 CFM per SQFT	Covers up to 3,750 SQFT
Amps	Hi: 2.17 / Med: 1.03 / Low: 0.34
Motor Voltage	120 VAC, 60 Hz
# of Speeds	3
Motor Head Diameter	16.5″
Motor Head Length	10"
Controls	QuietCool Smart Control Hub
Fire Shut-off	182 °F
Warranty	15 Years
Shipping Weight	19 lbs.
Box Dimensions	H:22.5" x W:19.75" x D:11.25"
In The Box	-AFG SMT ES-3.0 -Smart Control Hub
	-Accessory Bag -Vent Covers

Features & Benefits:

- Variable 3-speed Ultra-Energy Efficient ECM
- QuietCool Smart App Control
- Anti-Vibration Pads

- Fire Safety Sense Shut-off
- Plug and play (no wiring)
- Vent Covers
- This fan can consistently keep the attic cooler than a traditional attic fan



For more information, visit our website at: OUIETCOOLSYSTEMS.COM



